

STC Solenoid Valve List Price

To Order, Please Specify: 1. Model No. 2. Voltage

	Part No.	List Price	Port Size (NPT)	Cv	Voltage	Features		
	2W025-08	\$18.00	1/4	0.23	Voltage Options: 1 = 12 VDC 2 = 24VDC 3 = 110VAC 4 = 220VAC	2 Way, Direct Acting, Normally Closed Brass Body Seals: NBR Operating Temp: -5 to 80 deg. C Operating Pressure: 145 PSI Coil: F Class, IP65, 100% ED Service: Air, Water, Oil		
	2W040-10	\$31.05	3/8	0.6				
	2W160-10	\$49.50	3/8	4.8				
	2W160-15	\$49.50	1/2	4.8				
	2W200-20	\$57.15	3/4	7.6				
	2W250-25	\$69.75	1	12				
	2W400-40	\$171.00	1 1/2	29				
2W500-50	\$248.40	2	48					
	2L170-10		3/8	4.8			Voltage Options: 1 = 12 VDC 2 = 24VDC 3 = 110VAC 4 = 220VAC	2 Way, Direct Acting, Normally Closed Brass Body, Seals: PTFE Operating Temp: -5 to 150 deg. C Operating Pressure: 215 PSI Coil: F Class, IP65, 100% ED Service: Air, Water, Steam
	2L170-15	\$94.05	1/2	4.8				
	2L170-20	\$106.65	3/4	4.8				
	2L170-25	\$119.25	1	12				
	2L170-35		1 1/4	20				
	2L170-40	\$196.65	1 1/2	20				
	2L170-50		2	48				
	VX2120-06		1/8	0.33	Voltage Options: 1 = 12 VDC 2 = 24VDC 3 = 110VAC 4 = 220VAC	2 Way, Direct Acting, Normally Closed Brass Body, Seals: VITON Operating Temp -5 to 150 deg. C Operating Pressure: 140 PSI Coil: F Class, IP65, 100% ED Service: Air, Water, Steam		
	VX2120-08		1/4	0.33				
	VX2120-10		3/8	4				
	VX2120-15		1/2	4				
	VXF2120-06		1/8		Voltage Options: 1 = 12 VDC 2 = 24VDC 3 = 110VAC 4 = 220VAC	2 Way, Direct Acting, Normally Closed Stainless Steel Body; Seals: VITON Operating Temp: -5 to 150 deg. C Operating Pressure: 150 PSI Coil: F Class, IP65, 100% ED Service: Liquid		
	VXF2120-08		1/4					
	VXF2120-10		3/8					
	VXF2120-15		1/2					
	2S025	\$27.90	1/4	0.23	Voltage Options: 1 = 12 VDC 2 = 24VDC 3 = 110VAC 4 = 220VAC	2 Way, Direct Acting, Normally Closed 304 Stainless Steel Body; Seals: VITON Operating Temp -5 to 150 deg. C Operating Pressure: 150 PSI Coil: F Class, IP65, 100% ED Service: Air, Water, Oil		
	2S040	\$38.70	3/8	0.6				
	2P-06	\$16.75	1/8	0.23	Voltage Options: 1 = 12 VDC 2 = 24VDC 3 = 110VAC 4 = 220VAC	2 Way, Direct Acting, Normally Closed Engineered Plastic Body; Seals: NBR Operating Temp -5 to 80 deg. C Operating Pressure: 100 PSI Coil: F Class, IP65, 100% ED Service: Air, Liquid		
	2P-08	\$16.75	1/4	0.23				
	QW-25		1	12	Pilot Pressure: 80-150 PSI	2 Way, Direct Acting, NC or NO Brass Body; Seals: Viton Operating Temp -5 to 150 deg. C Operating Pressure: 145 PSI Air Pilot Pressure: 80-150 PSI Service: Air, Water, Oil, Gas		
	QW-40		1 1/2	29				
	QW-50		2	48				